

# AIR COMPRESSORS

## 30 & 80-Gallon Two Stage Gasoline

Two stage air compressors provide a reliable air source for commercial, industrial and automotive applications.



### Compressor Pump

- ✓ Stainless-steel braided discharge hose
- ✓ Oil level sight indicator

### Engine

- ✓ Electric start standard (battery and cables not included)

### Frame

- ✓ Powder coated ASME coded 30 or 80-gallon receiver tank (Tank-mounted models only)
- ✓ 3/8-inch base plate to reduce vibration
- ✓ 14-gauge powder coated two-piece belt guard
- ✓ Tabbed design offers flexible installation

### Components

- ✓ Regulator and two gauges for tank and outlet pressure
- ✓ ASME safety valves
- ✓ 16.5-inch fly wheel
- ✓ Tank drain valve

ABS-14S-30H

### TANK-MOUNTED MODELS

MODEL NUMBER	CFM @ PSI*	DISPLACEMENT/ENGINE	COMPRESSOR	CYLINDER	CRANKCASE	TANK SIZE	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
ABS-13H-30H	29.0 @ 175	389cc Honda OHV	Two stage	Cast iron	Splash lubricated cast iron	30-gallon	Pneumatic	42x19x45in.	480 lb.	416 lb.
ABS-14K-30H	29.0 @ 175	429cc Kohler OHV	Two stage	Cast iron	Splash lubricated cast iron	30-gallon	Cable throttle	42x19x45in.	480 lb.	416 lb.
ABS-14S-30H	29.0 @ 175	404cc Subaru OHC	Two stage	Cast iron	Splash lubricated cast iron	30-gallon	Cable throttle	42x19x45in.	480 lb.	416 lb.
ABS-13H-80H	29.0 @ 175	389cc Honda OHV	Two stage	Cast iron	Splash lubricated cast iron	80-gallon	Pneumatic	52x26.5x53in.	560 lb.	496 lb.
ABS-14S-80H	29.0 @ 175	404cc Subaru OHC	Two stage	Cast iron	Splash lubricated cast iron	80-gallon	Cable throttle	52x26.5x53in.	560 lb.	496 lb.

### BASE-MOUNTED MODELS

MODEL NUMBER	CFM @ PSI*	DISPLACEMENT/ENGINE	COMPRESSOR	CYLINDER	CRANKCASE	TANK SIZE	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
ABS-13H-B	29.0 @ 175	389cc Honda OHV	Two stage	Cast iron	Splash lubricated cast iron	Base-mount	Pneumatic	36.5x19x28in.	279 lb.	215 lb.
ABS-14S-B	29.0 @ 175	404cc Subaru OHC	Two stage	Cast iron	Splash lubricated cast iron	Base-mount	Cable throttle	36.5x19x28in.	279 lb.	215 lb.

\*Equipped with 150-PSI maximum rated regulator.

### Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
3-0304	Pump	All models	AW-6000-1002	Equipment cover	All models
33-0548	Cable throttle control	Honda models	IX-0001	Vibration pads	Tank-mounted models
854-0093	Service truck mount kit (recommended for models that are mounted in service truck applications)	All models			