

AIR COMPRESSORS

8-Gallon Two Stage Gasoline

Ideal for both contractors and remodelers, this two stage air compressor provides a reliable air source on remote jobsites.



AM2-PR09-08M

Compressor Pump

- ✓ Stainless-steel braided discharge hose
- ✓ Large canister intake filter

Frame

- ✓ Powder coated 8-gallon twin tank receivers
- ✓ $\frac{3}{16}$ -inch base plate to reduce vibration
- ✓ 14-gauge powder coated two-piece belt guard

Components

- ✓ Regulator and two gauges for tank and outlet pressure
- ✓ Manual drain valves for proper maintenance
- ✓ 16.5-inch fly wheel
- ✓ Quality pilot valve unloader

MODEL NUMBER	CFM @ PSI*	DISPLACEMENT/ENGINE	COMPRESSOR	CYLINDER	CRANKCASE	TANK SIZE	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
AM2-PH09-08M	17.2 @ 175	270cc Honda OHV	Two stage	Cast iron	Splash lubricated cast iron	8-gallon	Pneumatic	44x26x31in.	330 lb.	260 lb.
AM2-PK95-08M	17.2 @ 175	277cc Kohler OHV	Two stage	Cast iron	Splash lubricated cast iron	8-gallon	Cable throttle	44x26x31in.	330 lb.	260 lb.
AM2-PR09-08M	17.2 @ 175	265cc Subaru OHC	Two stage	Cast iron	Splash lubricated cast iron	8-gallon	Pneumatic	44x26x31in.	330 lb.	260 lb.

*Equipped with 150-PSI maximum rated regulator.

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
33-0294	Cable throttle control	AM2-PH09-08M	AX-0003	Manual drain/regulator/metal bowl	All models
33-0401	Cable throttle control	AM2-PR09-08M	AX-0015	Electric start (battery and cables not included)	AM2-PH09-08M
AW-6000-1002	Equipment cover	All models	AX-0041	Electric start (battery and cables not included)	AM2-PR09-08M