

# HDC SERIES

## HOT WATER PRESSURE WASHERS



Designed with professional contract cleaners in mind, the HDS Series is perfect for the heaviest construction applications, and durable enough to handle 24-hours-a-day, seven-days-a-week run-time.

### Gasoline - Belt Drive

- High quality fuel filter/water separator ensures clean fuel supply to the burner
- Stainless-steel coil wrap prevents rusting
- 12-volt burner (battery not included)
- Large polyethylene float tank
- 1/2-inch schedule 80-coil with stainless-steel wrap heat exchanger
- On/Off burner switch
- Adjustable high pressure detergent injection
- Electric start engine
- 10-gallon polyethylene burner fuel tank
- 10-gallon polyethylene engine fuel tank



*HDC-3505-0K6G  
shown with optional adjustable  
temperature control HX-0212*

#### **Additional Features:**

##### **Pump**

- Belt drive triplex piston General or AR pump with ceramic plungers
- Factory preset unloader

##### **Engine**

- Performance-proven industrial gasoline engine with electric start (battery not included)

##### **Frame**

- Heavy-duty powder coated steel tube frame

##### **Components**

- No.1 or No.2 diesel or kerosene fired burner (Bio-fuel not approved at this time)
- Pressure relief valve protects against excessive system pressure

#### **Units Include:**

- 50-foot x  $\frac{3}{8}$ -inch steel wire-braided pressure hose with quick connects
- Professional-grade insulated trigger gun with safety lock-off
- Adjustable pressure insulated dual lance
- Adjustable high pressure detergent injection

#### **Miscellaneous:**

- Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F

# HDC Series

Model Number	PSI	GPM	Displacement/Engine	Gas Tank Capacity	Burner Fuel Tank Capacity	Fuel Consumption	BTU per hour	Dimensions	Ship Wt.	Net Wt.
HDC-3005-0K6G	3000	4.8	624cc Kohler	10.0 gallon	10.0 gallon	2.76 gph	386,400	50in.x34in.x46in.	844 lb.	725 lb.
HDC-3005-0V6G	3000	4.8	480cc Vanguard OHV	10.0 gallon	10.0 gallon	2.76 gph	386,400	50in.x34in.x46in.	844 lb.	725 lb.
HDC-3505-1H6G	3500	4.7	GX630 Honda OHV	10.0 gallon	10.0 gallon	2.76 gph	386,400	50in.x34in.x46in.	844 lb.	725 lb.
HDC-3505-0K6G#	3500	4.7	624cc Kohler	10.0 gallon	10.0 gallon	2.76 gph	386,400	50in.x34in.x46in.	844 lb.	725 lb.
HDC-4004-1H6A	4000	4.0	GX630 Honda OHV	10.0 gallon	10.0 gallon	2.45 gph	343,000	50in.x34in.x46in.	844 lb.	725 lb.

#Higher performance 624cc Kohler engine.

## OPTIONS

Part Number	Description	Fits Models
HX-0130	<b>Three-way ball valve</b> - Allows pressure washer to be operated from garden hose/float tank or trailer supply tank by adjusting ball lever valve	All models
HX-0147	<b>Four-point lifting capability</b> - Allows unit to be lifted by crane	All models
HX-0156	<b>Hour meter</b> - Displays number of hours unit has been in operation	All models
HX-0200	<b>Trapping unloader</b> - For longer hose runs and cleaning elevated areas	All models
HX-0212	<b>Adjustable temperature control</b> - Operator is able to adjust outlet water temperature between 96°F-250°F	All models
HX-0229	<b>Clutch drive option</b> - Stops the pump from spinning in bypass mode and helps to extend the life of the pump	3000 PSI models
HX-0230	<b>Clutch drive option</b> - Stops the pump from spinning in bypass mode and helps to extend the life of the pump	3500 PSI models

## ACCESSORIES

Part Number	Description	Fits Models
AW-5740-0000	<b>Wheel kit</b> - Allows unit to become portable	All models
AW-6000-1006	<b>Hot water skid equipment cover</b> - Keeps your equipment clean, dry and looking like new, made from 600-denier vinyl-backed polyester, water resistant, drawstrings to secure cover	All models
50-0170	<b>Stack adapter</b> - Allows 8-inch flue pipe to be installed to boiler exhaust port	All models
850-0324	<b>Gasket (for 50-0170)</b> - Seals between 50-0170 stack adapter and boiler housing	All models

POWERED by **HONDA**™

