




ChoreMaster® Series

Commercial Gasoline
3600-Watt up to 8000-Watt

Transport dependable power where it's needed most with the ChoreMaster generators. These units are equipped for any project or power outage.



GEN-6500-0MM1

ALTERNATOR

- Copper and aluminum windings (Copper windings on GEN-8000-0MM1E)

ENGINE

- Recoil start (GEN-8000-0MM1E also has electric start – sealed battery included)

FRAME

- Powder coated wraparound frame
- Handle, wheels and outlet covers (GEN-6500 and GEN-8000 models)

COMPONENTS

- Fuel shut-off valve
- DC/battery charging (GEN-3600-0MM0)
- Equipped with CO detector with automatic shutdown (GEN-6500 and GEN-8000 models)
- Idle control (GEN-6500 and GEN-8000 models)
- Digital display for voltage, hertz, run hours and total hours (GEN-6500 and GEN-8000 models)
- USDA/USFS-approved spark arrestors

LIMITED WARRANTY

- 3 year engine

CERTIFICATION

- CSA Certified

MODEL NUMBER	GEN-3600-0MM0	GEN-6500-0MM1	GEN-8000-0MM1E
MAX. AC OUTPUT	3600 watts	6500 watts	8000 watts
RATED AC OUTPUT	3000 watts	6500 watts	7200 watts
DISPLACEMENT/ENGINE	212cc Mi-T-M OHV	420cc Mi-T-M OHV	420cc Mi-T-M OHV
ALTERNATOR	Brushed 120V, 60Hz	Brushed 120V/240V, 60Hz	Brushed 120V/240V, 60Hz
MAX. AMPS (120V/240V)	30.0	54.1/27.0	66.6/33.3
CONT. AMPS (120V/240V)	25.0	54.1/27.0	60.0/30.0
RECEPTACLES	(2) 120V, 20A GFCI duplex (1) 120V, 30A twist lock (1) 12V DC 8.3A	(2) 120V, 20A GFCI duplex (1) 120V, 30A twist lock (1) 120V/240V, 30A twist lock	(2) 120V, 20A GFCI duplex (1) 120V, 30A twist lock (1) 120V/240V, 30A twist lock
CIRCUIT BREAKERS	(1) Main circuit breaker (2) 20A toggle circuit breakers, single pole (1) 10A DC breaker	(1) Main circuit breaker (2) 20A toggle circuit breakers, single pole	(1) Main circuit breaker (2) 20A toggle circuit breakers, single pole
RATED SPEED	3600 RPM	3600 RPM	3600 RPM
DECIBEL RATING	72.0	80.0	85.0
FUEL CAPACITY	4.0 gallons	7.53 gallons	7.53 gallons
RUN TIME (AT FULL LOAD)	8.5 hours	8.8 hours	6.5 hours
DIMENSIONS (LxWxH)	24.9x17.6x17.9in.	27.8x20.2x21.6in.	27.8x20.2x21.6in.
SHIP WT.	134 lb.	210 lb.	218 lb.
NET WT.	102 lb.	183 lb.	192 lb.


Note: All gasoline models sold in California are required to have a CARB compliant engine and fuel system. Consult factory. Noise level tested at seven meters (75% load). Rating represents minimum noise level rating.

ChoreMaster® Series

Portable Generators – Commercial Gasoline – 3600-Watt up to 8000-Watt

ACCESSORIES:

PART NUMBER	DESCRIPTION	FITS MODELS
32-0915	RV generator adapter – 30A/125V female/male. Use to connect RV cordsets to 30A generators	All models
32-1289	Triple receptacle adapter – Converts (1) L5-30 plug to (3) lighted 5-20 locking receptacles	All models
AW-5090-0009	Lifting hook – For easier portability, folds down and out of the way when not in use	GEN-3600-0MM0
AW-6000-1002	Equipment cover – Keeps your equipment clean, dry and looking like new	GEN-6500-0MM1 & GEN-8000-0MM1E



GFCI 5-20R
All Models



NEMA L5-30R
120VAC
All Models



NEMA L14-30R
120V/240V
GEN-6500 &
GEN-8000
Models

EQUIPPED WITH
CO DETECTOR



 **WARNING:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov.