

14000-Watt

Industrial Gasoline

The most grueling jobs are no match for the 14000-watt generator, and it's designed to move easily from one job to the next.



ALTERNATOR

- Total harmonic distortion (THD) less than 5%
- Copper windings

ENGINE

• Electric start – sealed battery included

FRAME

- Reinforced powder coated steel frame
- 13-inch flat-free tires

COMPONENTS

- Easy-access and protected control panel with magnetic circuit breakers and GFCI-protected receptacles
- · Large low tone muffler
- · Easy-to-read fuel gauge
- Idle control
- Voltmeter/hour meter
- · Heavy-duty industrial air cleaner
- USDA/USFS-approved spark arrestors

LIMITED WARRANTY

• 3 year engine

CERTIFICATION

• CSA Certified (GEN-14000-1MHE)

MODEL NUMBER	CEN 14000 1MHE	CEN 14000 1MMF
MODEL NUMBER	GEN-14000-1MHE	GEN-14000-1MME
MAX. AC OUTPUT	14000 watts	14000 watts
RATED AC OUTPUT	12000 watts	12000 watts
DISPLACEMENT/ENGINE	688cc Honda GX630 OHV+	670cc Mi-T-M OHV
ALTERNATOR	Brushless 120V/240V, 60Hz	Brushless 120V/240V, 60Hz
MAX. AMPS (120V/240V)	116.7/58.3	116.7/58.3
CONT. AMPS (120V/240V)	100.0/50.0	100.0/50.0
RECEPTACLES	(2) 120V, 20A GFCI duplex (1) 120V, 30A twist lock (1) 120V/240V, 30A twist lock (1) 120V/240V, 50A	(2) 120V, 20A GFCI duplex (1) 120V, 30A twist lock (1) 120V/240V, 30A twist lock (1) 120V/240V, 50A
CIRCUIT BREAKERS	(2) 20A toggle circuit breakers, single pole (1) 30A toggle circuit breaker, single pole (1) 30A toggle circuit breaker, double pole (1) 50A toggle circuit breaker, double pole	(2) 20A toggle circuit breakers, single pole(1) 30A toggle circuit breaker, single pole(1) 30A toggle circuit breaker, double pole(1) 50A toggle circuit breaker, double pole
RATED SPEED	3600 RPM	3600 RPM
DECIBEL RATING	77.5	80.0
FUEL CAPACITY	13.2 gallons	13.2 gallons
RUN TIME (AT FULL LOAD)	8.0 hours	8.0 hours
DIMENSIONS (LxWxH)	31.5x30.5x37.5in.	31.5x30.5x37.5in.
SHIP WT.	568 lb.	553 lb.
NET WT.	508 lb.	493 lb.
Noise level tested at seven meters (75% I	oad). Rating represents minimum noise level rating.	

Noise level tested at seven meters (75% load). Rating represents minimum noise level rating. +49 state engine. Not for sale in California.

14000-Watt

Portable Generators - Industrial Gasoline

ACCESSORIES: PART NUMBER DESCRIPTION FITS MODEL 32-0915 RV generator adapter – 30A/125V female/male. Use to connect RV cordsets to 30A generators. All models 32-1289 Triple receptacle adapter – Converts (1) L5-30 plug to (3) lighted 5-20 locking receptacles All models AW-6000-1002 Equipment cover – Keeps your equipment clean, dry and looking like new All models

OPTIONS: Options must be ordered with unit and cannot be added later.

PART NUMBER	DESCRIPTION	FITS MODEL
GX-0003	Skid feet – For stationary applications	All models
GX-0005	50A twist lock receptacle - Marine receptacle for routine marine applications	All models











NEMA L14-30R NEMA 14-50R NEMA L5-30R 120V/240V 50A 120VAC

GX-0005 option CS6369A 50A twist lock receptacle





WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.