

Skid Gasoline/Diesel

Belt Drive - HDB Series

The powder coated steel frame of the HDB Series offers durability and resilience in demanding conditions.



PUMP

- Belt drive triplex piston pump with ceramic plungers
- · Factory preset unloader

ENGINE

 Performance-proven engine with electric start – battery not included

FRAME

- Powder coated steel skid frame
- Stainless-steel removable front panel
- Optional wheel kit with locking tire brake and four tires

COMPONENTS

- Stainless-steel coil wrap heat exchanger with horizontal schedule 80 pipe coil
- 12V Beckett burner battery not included
- No. 1 or No. 2 diesel or kerosene fired burner (Not approved for bio-fuel)
- · Adjustable thermostat
- Low pressure detergent injector

MISCELLANEOUS

 Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F

UNIT INCLUDES

- Quick connect nozzles 0°, 15°, 25° and 40°
- 50-foot x %-inch high pressure hose with quick connects
- Adjustable pressure insulated dual lance with trigger gun

LIMITED WARRANTY

• 3 year engine

CERTIFICATION

CSA Certified – US and Canada

GASOLINE MODELS

MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	TANK CAPACITY	TANK CAPACITY	CONSUMPTION	BTU PER HOUR	(LxWxH)	SHIP WT.	NET WT.
HDB-3004-0H6G	3000	3.9	389cc Honda GX390 OHV+	General	1.7 gallons	10.0 gallons	2.76 gph	386,400	53.5x28.75x42in.	685 lb.	566 lb.
HDB-4004-0H6G	4000	3.7	389cc Honda GX390 OHV+	General	1.61 gallons	10.0 gallons	2.76 gph	386,400	53x28.5x42in.	685 lb.	566 lb.
HDB-4004-0V6G	4000	3.7	408cc Vanguard OHV+	General	1.51 gallons	10.0 gallons	2.76 gph	386,400	53x28.5x42in.	685 lb.	566 lb.

Note: All gasoline models sold in California are required to have a CARB compliant engine. Consult factory.

+49 state engine. Not for sale in California

DIESEL MODEL

MODEL NUMBER	PSI	GPM	HORSEPOWER/ENGINE	PUMP	ENGINE FUEL TANK CAPACITY	BURNER FUEL TANK CAPACITY	BURNER FUEL CONSUMPTION	BTU PER HOUR	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
HDB-3004-0K7G	3000	3.9	9.1 HP Kohler KD440 OHV	General	1.3 gallons	10.0 gallons	2.76 gph	386,4000	53.5x28.75x42in.	745 lb.	626 lb.

Skid Gasoline/Diesel

Hot Water - Belt Drive - HDB Series

ACCESSORIES: PART NUMBER DESCRIPTION FITS MODELS 50-0170 Stack adapter - Allows 8-inch flue pipe to be installed to boiler exhaust port All models 850-0324 Gasket – Seals between 50-0170 stack adapter and boiler housing All models AW-5740-0014 Wheel kit - 4 rubber wheels allow the unit to become portable All models AW-5740-0015 Caster wheel kit - Includes 2 caster wheels and 2 rubber wheels for easier movement on flat surfaces All models AW-6000-1006 Hot water equipment cover - Keeps your equipment clean, dry and looking like new, made from 600-denier vinyl-backed polyester, water resistant, drawstrings All models to secure cover; Mi-T-M logo AW-6000-1007 Hot water equipment cover - Keeps your equipment clean, dry and looking like new, made from 600-denier vinyl-backed polyester, water resistant, drawstrings All models to secure cover; no logo

OPTIONS: Options must be ordered with unit and cannot be added later.

PART NUMBER	DESCRIPTION	FITS MODELS
HX-0156	Hour meter – Displays the number of hours unit has been in operation	All models
HX-0176*	Steam – Increases outlet temperature to 250°F	All models
HX-0220	High pressure chemical, K7 – Adjustable high pressure chemical, includes float tank	All models
HX-0221*	High pressure chemical, trapping unloader – Adjustable high pressure chemical, includes float tank	All models
HX-0225	Trapping unloader – For hose runs longer than 50-foot and for cleaning elevated areas	HDB-3004-0H6G & HDB-3004-0K7G
HX-0226	Three-way ball valve – Allows the pressure washer to be operated from garden hose, float tank or trailer supply tank by adjusting ball lever valve	All models

^{*}Trapping unloader is required for ordering the HX-0221 high pressure chemical option or HX-0176 steam option. HDB-4004 models come standard with a trapping unloader; HDB-3004 models must add the HX-0225 option.





WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.